



UNI EN 1090-1:2009+A1:2011
EXECUTION OF STEEL STRUCTURES AND ALUMINIUM STRUCTURES

DECLARATION OF PERFORMANCE

1. COD: KN500

2. INTENDED USE: Glass clamp for floor , glass thickness range 12-12,76mm

3. PRODUCER:

INOXA AB
Fisksätravägen 34, 13342
Saltsjöbaden SWEDEN

5. SYSTEM OF EVALUATION (VVCP): 2+

6a. HARMONIZED STANDARD

EN1090-1:2009+A1:2011

NOTIFIED BODY

The notified body **Istituto Giordano** issued the certificate of conformity of the factory production control n. **0407-CPR-879**, based on the following elements:

- i) initial inspection of factory and of factory production control;
- ii) monitoring, assessment and evaluation of factory production control.

7. PERFORMANCE

Geometric tolerances	EN 1090-2
Weldability	Stainless steel AISI 316 UNI EN 10088-2
Yield strength	240 N/mm ²
Reaction to fire	Class A1
Release of cadmium	Not applicable
Release of radioactivity	Not applicable
Durability	Not applicable
Structural features	Not applicable
Manufacturing	according EN 1090-2 – EXC1

8. DECLARATION: The supply of the product referred to in paragraphs 1 and 2 is in conformity with the declared performance in point 7

08.07.2015

The Legal Representative

INOXA AB
Fisksätravägen 34
133 42 Saltsjöbaden

